

# Fo-Poxy (Aliccoat)

## ***DESCRIPTION:***

A two component Aliphatic Polyurethane with excellent color and gloss stability, resistant to chemicals, waterproof coating. Its beauty, durability and overall performance are unsurpassed by any other painting system. High flexibility ensures firm grip on metal surface even during vibration where most other paint system crack

## ***PRINCIPAL USES:***

Developed for quality painting of metal surfaces, wood, concrete, asbestos, cement, where excellent gloss retention, abrasion and chemical resistance are desired. Recommended for industrial plants, machinery such as pump externals, valves and other equipment which face corrosion problem as well as undergo vibrational stress

## ***FEATURES AND BENEFITS:***

- Excellent color and gloss retention after prolonged exposure to weathering.
- Watertight-It dries to a very hard film that serves as a watertight finish
- Maximum abrasion resistance-It has exceptional abrasion resistance for a paint film, and is able to withstand repeated scratching, scrubbing and repeated detergent washing.
- Excellent resistance to stains, solvents and most chemicals. It is also a highly durable finish for industrial plants because of its strong resistance to chemical attacks, pollution and corrosive industrial environments.

***COVERAGE*** : 4-5 sq. mtrs. per Kg. mix

***COLOUR*** : A variety of colours available.

## ***MANUFACTURED BY :***

**AQUADRA FORSPEC PVT. LTD., Mumbai, India**

Tel. : 022- 2884 5705

Fax : 022- 2887 2661

E-mail : aquadra@vsnl.com

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use thereof.