

AQ SEAL

Epoxy Putty

AQ SEAL is a versatile, hand-kneadable, 1 : 1 ratio, easy to use, epoxy putty.

- Bonds to metal, wood, glass, concrete, fiberglass, plastics, etc.
- Soft as Clay, Cures Hard as Steel.
- Sets in 60 minutes.

Features :

- » Hardens quickly
- » Chemical Resistant
- » Solvent Free
- » Good Di-electric Strength
- » Temperature Resistant
- » Does not shrink
- » Can be drilled & painted after cure.
- » High Mechanical Strength

Uses :

Seals leakages, Patch pipes, Fill castings blow holes, Bond broken parts, plumbing, electrical insulation, Fixes damaged parts, Construction Sealant.

Directions :

- ⇒ For best results, clean and roughen the bond area prior to application
- ⇒ Cut out the required amount with a knife , in equal weight proportions
- ⇒ Knead with fingers and briskly roll between palms to a uniform colour
- ⇒ Apply to surface to be repaired within 15 minutes of mixing
- ⇒ Force the material into any cracks or holes to be filled

Technical Data :

WORKING LIFE	20 minutes
WORKING TEMPERATURE	100 ° C
COMPLETE CURE TIME	24 Hours
HARDNESS	80 Shores D
COMPRESSIVE STRENGTH	800 Kgs./sq. cm.
TENSILE SHEAR STRENGTH	75 Kgs./sq.cm.
FLEXURAL STRENGTH	450 Kgs./sq.cm.

Packing : Available in 100 gms, 1 Kg, and bulk packing.

MANUFACTURED BY :

AQUADRA FORSPEC PVT. LTD.

Tel. : 022- 2884 5705
Email : aquadra@vsnl.com

Fax : 022- 2887 2661
URL : www.aquadra.com