

FP-COAT (EPOXY)

DESCRIPTION:

A two component high build epoxy coating with good resistance against chemicals. Its high strength, durability and overall performance are unsurpassed by any other painting system. Good flexibility ensures firm grip on metal surfaces even during vibration where most other coating systems crack.

PRINCIPAL USES:

Developed for quality coating of metal surfaces, wood, concrete, where abrasion and chemical resistance are desired. Recommended for industrial plants, piping, machinery such as pump externals, valves and other equipments which face corrosion problems as well as undergo vibrational stresses.

FEATURES AND BENEFITS:

- Watertight-It dries to a very hard film that serves as a watertight finish
- Abrasion resistance - It has good abrasion resistance.
- Excellent resistance to stains, solvents and most chemicals. It is also a highly durable finish for industrial plants because of its strong resistance to chemical attacks, pollution and corrosive industrial environments.

COLORS : A variety of colours available.

APPLICATION : By brush.

COVERAGE : 4 - 5 square meters per Kilogram mix

MANUFACTURED BY :

AQUADRA FORSPEC PVT. LTD., Mumbai, India

Tel. : 022- 2884 5705

Fax : 022- 2887 2661

E-mail : aquadra@vsnl.com

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use thereof.