

FO-POXY (E)

EMERGENCY REPAIR COMPOUND

DESCRIPTION

Fast Cure Cold Welding Compound, for emergency repair jobs. Can be used for the all types of ferrous and non-ferrous metals for quick, and effective leak sealing applications. Used for emergency repairs in critical applications. It reduces shutdown time drastically, since it has a very low curing time of approximately 10 minutes.

APPLICATION

Leaking pipelines, tank, cracked sumps and pans, leaking transformers, capacitor, reactor, tubes, pumps, threaded fittings, radiators & batteries.

PROPERTIES

<i>CURE TIME</i>	<i>(MINS.)</i>	<i>- 10</i>
<i>COMPRESSIVE STRENGTH</i>	<i>(KGS/CM²)</i>	<i>- 1093</i>
<i>TENSILE STRENGTH</i>	<i>(KGS/CM²)</i>	<i>- 250</i>
<i>FLEXURAL STRENGTH</i>	<i>(KGS/CM²)</i>	<i>- 530</i>
<i>HARDNESS</i>	<i>(SHORE D)</i>	<i>- 85</i>
<i>WITHSTANDING PRESSURE</i>	<i>(KGS/CM²)</i>	<i>- 100</i>
<i>MAXIMUM TEMPERATURE</i>	<i>(°C)</i>	<i>- 200</i>

CHEMICAL RESISTANCE

Doesn't react with common industrial gases, acids, reagents & solvents.

ADDITIONAL INFORMATION

Can be prepared as per client specification.

Coverage Area : 1070 sq. cm. / Kg for 5 mm product thickness.

MANUFACTURED & MARKETING BY :



**AQUADRA FORSPEC
PVT. LTD.**

Tel.: 022- 2884 5705 Fax : 2887 2661 Email : aquadra@vsnl.com

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use thereof.